

AGRIXTRA H

- Super volume R1W tire optimized for improved flotation and heavy loads up to 40 mph – load range D
- Designed for both harvester and floater (spreader) applications



Metric Size	Load Index	Weight (lbs)	T.D. (32nds)	GFP (sq in)
620/75R26	166A8/B	501	66	360
750/50R26	166D	425	48	346
750/65R26	166D	529	71	419
620/75R30	168D	476	73	380
650/75R32	172D	690	73	427
800/65R32	178D	690	73	509
800/70R32	181D	813	73	560
900/60R32	181D	772	72	560
1000/50R25	172D	849	72	499
1050/50R32	184D	1006	76	733
1250/50R32	194D	1255	81	870

FLOTXTRA

- Radial steel constructed implement tire designed for high loads and speeds up to 40 mph (70 kph) – load range D
- Optimized for both transportation or forage equipment
- High durability, long tread life and improved lateral stability



Metric Size	Load Index	Weight (lbs)	T.D. (32nds)	GFP (sq in)
605/70R20.5	176F	410	23	261
500/60R22.5	155D	258	24	210
500/60R22.5	161D	258	24	210
560/45R22.5	152D	212	24	193
560/60R22.5	161D	298	24	251
560/60R22.5	165D	298	24	251
600/50R22.5	159D	286	24	237
600/50R22.5	167D	286	24	237
710/35R22.5	157D	252	24	221
710/40R22.5	161D	321	24	251
600/55R26.5	165D	353	25	279
650/55R26.5	169D	381	25	315
710/50R26.5	170D	435	25	326
800/45R26.5	174D	481	25	364
600/60R30.5	173D	455	29	325
650/65R30.5	176D	534	29	385
710/50R30.5	173D	497	29	353
750/60R30.5	181D	603	30	448

MAXAM

MAXAM TIRE INTERNATIONAL

300 Rosewood Drive, Suite 102, Danvers, MA 01923 U.S.A.
T. 844-MAXAM-NA F. 978-560-0624

MAXAMTIRE.COM

RADIAL AG LIMITED WARRANTY

The below Limited Warranty and Adjustment Policy is a commitment of tire replacement under certain specified conditions as provided below. This warranty policy applies to all MAXAM radial agricultural tires as specified below and does not require the existence of a defect to be considered eligible for an adjustment.

Agricultural Use*	Stubble Damage or Field Hazard Coverage	Scraper Application Use*
Up to Eight Years	With Stubble Prevention Device	With Appropriate Weight & Air Pressure Settings
Year 1 100%*	Year 1 80%	Year 1 80%
Year 2 100%*	Year 2 60%	Year 2 60%
Year 3 80%	Year 3 40%	Year 3 40%
Year 4 70%	Year 4 20%	Year 4 20%
Year 5 60%	Year 5 No Coverage	Year 5 No Coverage
Year 6 50%	Year 6 No Coverage	Year 6 No Coverage
Year 7 30%	Year 7 No Coverage	Year 7 No Coverage
Year 8 20%	Year 8 No Coverage	Year 8 No Coverage

* 100% FREE REPLACEMENT

See warranty document for policy details & conditions

PRODUCT ELIGIBILITY

All MAXAM brand radial agricultural tires manufactured and/or sold after January 1, 2018 and distributed by MAXAM per its identification code and production date. This policy applies to either the original owner, the user of the tires or the original purchaser of the agricultural equipment mounted with the tires. The MAXAM agricultural tires covered by this warranty policy belong to the following family of radial products: AGRIXTRA 85, AGRIXTRA 70, AGRIXTRA 65, AGRIXTRA XL, AGRIXTRA H, AGRIXTRA N & FLOTXTRA.

For complete details on the MAXAM Radial Ag Limited Warranty, please visit our website: www.maxamtire.com or contact us at 1-844-MAXAM-NA

MAXAM



RADIAL AGRICULTURAL TIRES

MAXAMTIRE.COM

**BUSINESS SOLUTIONS
PROVIDER**

AGRIXTRA 85

- Standard sized R1W tire for varied farming operations
- Designed for ag machinery applications from tractors to harvesters



Metric Size	US Equivalent	Load Index	Weight (lbs)	T.D. (32nds)	GFP (sq in)
250/85R24	9.5R24	109A8/B	86	48	109
280/85R24	11.2R24	115A8/B	99	50	128
320/85R24	12.4R24	122A8/B	124	52	158
340/85R24	13.6R24	125A8/B	137	53	174
380/85R24	14.9R24	131A8/B	169	54	206
420/85R24	16.9R24	137A8/B	201	58	243
280/85R28	11.2R28	118A8/B	114	50	139
320/85R28	12.4R28	124A8/B	134	52	169
340/85R28	13.6R28	127A8/B	150	53	185
380/85R28	14.9R28	133A8/B	184	54	217
420/85R28	16.9R28	139A8/B	221	58	256
380/85R30	14.9R30	135A8/B	200	54	230
420/85R30	16.9R30	140A8/B	236	63	264
460/85R30	18.4R30	145A8/B	271	64	306
320/85R32	12.4R32	126A8/B	150	52	179
380/85R34	14.9R34	146A8/B	212	54	237
420/85R34	16.9R34	142A8/B	260	63	280
460/85R34	18.4R34	147A8/B	300	64	325
320/85R36	12.4R36	128A8/B	163	52	190
340/85R36	13.6R36	132A8/B	192	58	211
340/85R38	13.6R38	133A8/B	198	58	217
380/80R38	14.9R38	142A8/B	212	57	210
420/85R38	16.9R38	144A8/B	280	63	295
460/85R38	18.4R38	149A8/B	326	64	343
520/85R38	20.8R38	155A8/B	404	67	409
460/85R42	18.4R42	156A8/B	399	64	422
480/80R42	18.4R42	151A8/B	373	64	364
520/85R42	20.8R42	157A8/B	448	67	435
520/85R42	20.8R42	167D	485	67	431
480/80R46	18.4R46	158A8/B	417	64	336
520/85R46	20.8R46	158A8/B	496	69	449
480/80R50	18.4R50	176A8/B	549	66	358

AGRIXTRA 70

- Premium R1W traction tire designed for wide tread field applications
- Designed to carry the same load capacity at both 25 & 30 mph



Metric Size	Load Index	Weight (lbs)	T.D. (32nds)	GFP (sq in)
360/70R24	122A8/B	139	50	158
380/70R24	125A8/B	156	52	174
420/70R24	130A8/B	182	53	201
480/70R24	138D	182	55	249
360/70R28	125A8/B	148	50	174
380/70R28	127A8/B	170	52	185
420/70R28	133A8/B	198	53	217
480/70R28	140A8/B	249	55	264
480/70R30	152D	265	60	272
520/70R30	145A8/B	304	63	306
480/70R34	155A8/B	288	60	288
520/70R34	148A8/B	332	63	332
480/70R38	145A8/B	319	57	306
520/70R38	150A8/B	366	63	354
580/70R38	155A8/B	444	71	409
620/70R42	160D	512	73	419
620/70R42	166D	512	73	419

AGRIXTRA XL

- Large volume R1W tire designed for high horsepower tractors and harvesters
- Designed to operate in the field, on the road and in scraping applications



Metric Size	Load Index	Weight (lbs)	T.D. (32nds)	GFP (sq in)
600/65R28	154D	353	64	297
600/70R30	158D	397	64	336
650/65R34	161D	496	73	366
650/75R38	169D	586	76	459
650/85R38	173D	739	78	514
710/70R38	171D	690	78	487
710/70R42	173D	754	78	514
710/75R42	175D	795	78	546
800/70R38	178D	690	78	594

AGRIXTRA 65

- Premium R1W traction tire designed for wide tread field applications
- Designed for low pressure operations to reduce soil compaction



Metric Size	Load Index	Weight (lbs)	T.D. (32nds)	GFP (sq in)
440/65R24	128D	172	53	190
480/65R24	133D	198	54	217
540/65R24	140D	247	58	264
420/65R28	128D	170	52	190
440/65R28	131D	190	53	206
480/65R28	136D	216	54	236
540/65R28	142D	271	58	280
540/65R30	150D	300	63	288
540/65R34	145D	329	64	306
600/65R34	151D	375	66	364
540/65R38	147D	362	64	325
600/65R38	153D	401	66	385
650/65R38	157D	494	71	435
650/65R38	166D	529	71	434
650/65R42	164D	531	73	449

AGRIXTRA N

- R1W & R1 narrow tires designed for both field and road applications
- Optimized for high clearance or narrow crop applications
- Suitable for both tractors and self-propelled sprayers



Metric Size	Load Index	Weight (lbs)	T.D. (32nds)	GFP (sq in)
420/90R30	147A8/B	254	62	243
380/90R46	159A8/B	298	58	237
380/90R50	160A8/B	342	58	244
320/90R54	151A8/B	262	54	208
380/90R54	152A8/B	331	62	281
VF380/90R46	173D	342	58	321
VF380/105R50	176D	418	49	258
480/95R50*	164D	494	67	396

* in development